

Submersible Transmitter

ATM.ECO/N - Analog Level Transmitter



Customer benefits

- Entry level series into precision level measurement
- Excellent long term stability allow accurate measurements over a long period
- High measurement accuracy is ensured by sophisticated digital temperature compensation algorithms
- Fast customization thanks to configurable product design
- Available with overvoltage protection

Version: 25.04.2016

Technical Specifications

Pressure measuring range (mH2O)

	1 ... 5, (1)	> 5 ... 20	> 20 ... 250
Overpressure	3 bar	3 x FS (≥ 3 bar)	3 x FS
Burst pressure, (2)	> 200 bar	> 200 bar	> 200 bar
Accuracy, (3), (\pm % FS)	≤ 0.25	≤ 0.25	≤ 0.25
Total Error, (4) (\pm % FS)			
-5 ... 50°C, (typ. / max.)	$\leq 1.0 / 1.5$	$\leq 0.7 / 1.0$	$\leq 0.7 / 1.0$
-5 ... 80°C, (typ. / max.)	$\leq 2.0 / 2.5$	$\leq 1.0 / 1.5$	$\leq 1.0 / 1.5$
Response time, (typ.)	< 1ms / 10 ... 90% FS	< 1ms / 10 ... 90% FS	< 1ms / 10 ... 90% FS
Long term stability, (5)	< 0.5% FS / < 4 mbar	< 0.2% FS / < 4 mbar	< 0.1% FS / < 0.2% FS

(1) 0.5 mH2O on request

(2) Transducer

(3) Zero based accuracy according to DIN-16086, incl. hysteresis and repeatability at ambient temperature

(4) Total error including accuracy and temperature influences at maximum signal span (16 mA / 10 V DC)

(5) 1 year (typ. / max.), the long term stability can be improved by ageing (burn-in) the sensor

Temperature range

Operating temperature	-5 ... 80°C
Process temperature	-5 ... 80°C
Storage temperature	-40 ... 80°C

Electrical specifications

	4 ... 20 mA	0 ... 5 V	0 ... 10 V
Power supply	9 ... 33 VDC	10 ... 30 VDC	12 ... 30 VDC
Supply influence	< 0.05% FS	< 0.05% FS	< 0.05% FS
Current consumption		3 mA	3 mA
Circuit diagram			
Load resistance		$R_L > 10k\Omega$	$R_L > 10k\Omega$
Load influence	< 0.05% FS	< 0.05% FS	< 0.05% FS

Qualifications

	Standard	Level	Typical interferences
EN 60068-2-6	Vibration	10g (4 ... 2000 Hz / \pm 10 mmp)	
EN 60068-2-27	Shock	100g (impulse duration 6 ms)	
EN 55022	Emission, class B	< 30 dB μ V/m (0.03 ... 1 GHz)	
EN 61000-4-2	Electrostatic discharge	8 kV contact 15 kV air	
EN 61000-4-3	Irradiated RF	10V/m (0.08 ... 2.7 GHz, 3s)	Radio sets, wireless phones
EN 61000-4-4	Transients (burst)	4 kV	Motors, valves
EN 61000-4-5	Surge	Line-Line: 0.5 kV/42 Ω Line-Earth: 1 kV/42 Ω	Overvoltage
EN 61000-4-6	Conducted RF	3 V (0.15 ... 80 MHz, 3 s)	Frequency converters

Physical specifications

Materials	
Transducer	Stainless steel (316L / 1.4435)
Housing	Stainless steel (316L / 1.4404)
Seals	Viton (Standard), EPDM, Kalrez, NBR
Cable	PUR, FEP, PE, PVC
Weight (1)	145 g

(1) Specification for a ATM.ECO/N, closed, cable

Equipment

Overview

10.00.0091	Accessories overview
------------	----------------------

Additional documents

Operating and safety instructions

	Article number
10.88.0092	DMM029

Ordering information

		X. XXXX.	XXXX.	XX.	XXX
Type	ATM.ECO/N				
Pressure type	Gauge	1			
	Absolute (vacuum)	2			
Pressure measuring range	100 mbar ... 25 bar	XX			
Process connection	Closed (Fig. 1)	55			
	Closed, (1.4435), for ACS (Fig. 1)	59			
	Open (Fig. 2)	56			
	G 1/4 M (Fig. 3)	11			
	G 1/2 M (Fig. 3)	13			
	Customized	99			
Electrical connection	PE cable, black, IP 68 (4) (5)		13		
	PUR cable, black, IP 68 (4) (6)		15		
	FEP cable, black, IP 68 (4)		21		
	PVC cable, blue, IP 68, ACS certified (4)		14		
	Connectable version, IP68, M12 (Lumberg RSF4), (Fig. 4), (3)		07		
	Customized		99		
Output signal	0 ... 5 VDC		46		
	0 ... 10 VDC		47		
	4 ... 20 mA		05		
	4 ... 20 mA surge protection		08		
Accuracy	$\leq \pm 0.25 \% \text{ FS}$			1	
Temperature range	-5 ... 50°C compensated (allowed process temperature: -5 ... 50°C)			4	
	-5 ... 80°C compensated (allowed process temperature: -5 ... 80°C)			5	
Option 1					
Option 2	Electronics packed in gel: Gauge pressure				C
	Electronics packed in gel: Absolute pressure				D
Option 3	Ballast weight 1.4435				B
	Cutting ring connection G 1/2 M				
	Strain relief				
	Seals: Viton (standard)				U
	Seals: EPDM				S
	Seals: Kalrez (Level)				T
	Seals: NBR (ACS)				H
	Humidity filter element for gauge versions (only for PUR and PE cable)				Z

(3) Connector with required cable has to be ordered separately (KART100)

(4) Please specify the required cable length and medium

(5) Suitable for drinking water (food approved)

(6) For operating temperature $> 50^{\circ}\text{C}$, PE or FEP cable must be used

Technical drawings

Dimensions

Fig. 1 Closed version




Fig. 2 Open version




Fig. 3 With process connection





Fig. 4 Electrical connection, connectable



	A [mm]	B [mm]	C [mm]	D [mm]	Weight [g]
without ballast weight	88	84	on request*	119*	ca. 145
with ballast weight	175	171	on request*	201*	ca. 405

*C: Depending on process connection

Colour	2-wire	3-wire
white	+Vin	+Vin
yellow	Pout	GND
brown		Pout
grey	EP (only Ex)	

Specifications may change without notice.

STS Headquarters, Switzerland:
 STS Sensor Technik Sirmach AG
 Rütihofstrasse 8, 8370 Sirmach, Switzerland
 sales@stssensors.com | www.stssensors.com

STS France:
 STS France
 844 Route de la Caille, 74350 Allonzier la Caille, France
 info-fr@stssensors.com | www.stssensors.fr

STS Germany:
 STS Sensoren Transmitter Systeme GmbH
 Poststrasse 7, 71063 Sindelfingen, Germany
 info-de@stssensors.com | www.stssensors.de

STS Great Britain:
 STS Great Britain Ltd.
 Box 3942 | Warwick | CV34 9AE, United Kingdom
 contact@stssensors.com | www.stssensors.co.uk

STS Italy:
 STS Italia s.r.l.
 Via Gesù 5, 20090 Opera (Milano), Italy
 info-italia@stssensors.com | www.stssensors.it